


Linear slide cylinder Double acting single rod type clean room specifications

# LCM -P73 Series



● Bore size:  $\phi$  4.5,  $\phi$  6,  $\phi$  8



## Specifications

Descriptions		LCM -P73		
Bore size	mm	$\phi$ 4.5	$\phi$ 6	$\phi$ 8
Actuation		Double acting		
Working fluid		Compressed air		
Max. working pressure	MPa	0.7		
Min. working pressure	MPa	0.2		0.15
Withstanding pressure	MPa	1.05		
Ambient temperature	°C	0 to 60		
Port size		M3		
Stroke tolerance	mm	+1.0 0		
Working piston speed	mm/s	30 to 300		
Cushion		None	Rubber cushioned	
Lubrication		Not available		
Allowable energy absorption	J	Refer to the table on Page 1766.		

## Stroke length

Bore size (mm)	Standard stroke length (mm)	Min. stroke length with switch (mm)
$\phi$ 4.5	5, 10	5
$\phi$ 6	5, 10, 15	
$\phi$ 8	5, 10, 15, 20	

Note 1: Other than standard stroke length is not available.

## Switch specifications

Descriptions	Proximity 2 wire		Proximity 3 wire	
	F2H/F2V	F2YH/F2YV	F3H/F3V	F3YH/F3YV
Applications	Programmable controller		Programmable controller, relay	
Output method	-		NPN output	
Power voltage	-		10 to 28 VDC	
Load voltage	10 to 30 VDC	24 VDC $\pm$ 10%	30 VDC or less	
Load current	5 to 20 mA		100 mA or less	50 mA or less
Light	LED (ON lighting)	Red/green LED (ON lighting)	LED (ON lighting)	Red/green LED (ON lighting)
Leakage current	1 mA or less		10 $\mu$ A or less	

Note 1: The maximum load current 20mA is applied at 25°C. The current will be lower than 20mA if ambient temperature around switch is higher than 25°C. (5 to 10mA at 60°C)

### Cylinder weight

Unit: g

Stroke length (mm)	5		10		15		20		Additional weight
Bore size (mm)	Magnet + Without switch rail	Magnet + With switch rail	Magnet + Without switch rail	Magnet + With switch rail	Magnet + Without switch rail	Magnet + With switch rail	Magnet + Without switch rail	Magnet + With switch rail	Weight per switch
φ 4.5	45	49	45	49	-	-	-	-	10
φ 6	61	66	61	66	69	75	-	-	10
φ 8	87	92	87	92	108	114	108	114	10

### Theoretical thrust table

Unit: N

Bore size (mm)	Operating direction	Working pressure MPa					
		0.2	0.3	0.4	0.5	0.6	0.7
φ 4.5	Push	3.2	4.8	6.4	8.0	9.5	11.1
	Pull	2.6	3.8	5.1	6.4	7.7	9.0
φ 6	Push	5.6	8.5	11.3	14.1	16.9	19.7
	Pull	4.2	6.4	8.5	10.6	12.7	14.8
φ 8	Push	10.1	15.1	20.1	25.2	30.2	35.2
	Pull	8.6	13.0	17.3	21.6	25.9	30.2

SCP*2
CMK2
CMA2
SCM
SCG
SCA2
SCS
CKV2
CA/OV2
SSD
CAT
MDC2
MVC
SMD2
MSD*
FC*
STK
ULK*
JSK/M2
JSG
JSC3
USSD
USC
JSB3
LMB
STG
STS/L
LCS
LCG
<b>LCM</b>
LCT
LCY
STR2
UCA2
HCM
HCA
SRL2
SRG
SRM
SRT
MRL2
MRG2
SM-25
CAC3
UCAC
RCC2
MFC
SHC
GLC
Ending

 Linear side cylinder  
 Combined functions

## How to order

● Without switch

**LCM - 6 - 10 - R** ————— **J2 P73**

● With switch

**LCM - 6 - 10 - R - F2H - R - J2 P73**

**A** Bore size

**B** Stroke length

**C** Piping direction

**D** Switch model no.

**E** Switch quantity

**F** Option

**G** Clean room specifications

Symbol	Descriptions
<b>A Bore size (mm)</b>	
4.5	φ 4.5
6	φ 6
8	φ 8

		Bore size			
		φ 4.5	φ 6	φ 8	
<b>B</b> Stroke length (mm)	5	5	●	●	●
	10	10	●	●	●
	15	15	-	●	●
	20	20	-	-	●

<b>C Piping direction</b>	
R	Right viewed from rod end
L	Left viewed from rod end

<b>D Switch model no.</b>				
Axial lead wire	Radial lead wire	Contact	Indicator	Lead wire
<b>F2H*</b>	<b>F2V*</b>	Proximity	1 color indicator type	2-wire
<b>F3H*</b>	<b>F3V*</b>			3-wire
<b>F2YH*</b>	<b>F2YV*</b>		2 color indicator type	2-wire
<b>F3YH*</b>	<b>F3YV*</b>			3-wire

<b>*Lead wire length</b>	
Blank	1 m (standard)
3	3 m (option)

<b>E Switch quantity</b>	
R	1 on rod end
H	1 on head end
D	Two

<b>F Option</b>	
<b>M</b> Note 1	With magnet
<b>F1</b> Note 1, 2	With magnet + switch rail (switch groove 1 pc.)
<b>F2</b> Note 1	With magnet + switch rail (switch groove 2 pcs.)
<b>J*</b>	Dowel pin attached (* ... pin number)

<b>G Clean room specifications</b>	
<b>P73</b>	Vacuum treatment

### ⚠ Caution for model no. selection

Note 1: Selection not required when designating the switch type.

Note 2: Available only for φ 4.5.

<Example of model number>

**LCM-6-10-R-F2H-R-J2P73**

Model: Linear slide cylinder, double acting

- A** Bore size: φ 6 mm
- B** Stroke length: 10 mm
- C** Piping direction: Right viewed from rod end
- D** Switch model no.: Proximity switch F2H, lead wire 1m
- E** Switch quantity: One on rod end
- F** Option: Dowel pin attached (2 pc.)
- G** Clean room specifications: Vacuum treatment